



## 5350B

### General description

Nitto double coated tape 5350B consists of a black PET carrier coated with modified acrylic pressure sensitive adhesive. Mainly used for splicing of low surface energy plastic films.

### Construction



- Colourless modified acrylic adhesive
- Black PET carrier
- Colourless modified acrylic adhesive
- Paper release liner

### Characteristics

Nitto 5350B is a DC-splicing tape with good adhesion on different low surface energy plastic films.


This property in combination with high tack and temperature resistance makes the product ideal as a splicing tape.

The black colour makes detection of splice very easy.

### Application

Nitto 5350B is mainly used in extrusion/printing industry for splicing plastic films.

## CORE FUNCTION




TO ADHERE

### Features

- high temperature resistance
- detectable
- good adhesion
- high tack on low surfaces energy plastic films
- RoHS compliant (2011/65/EC, 2015/863)



Edition: January 2020  
Code: DS/01.11/ 5350B ENG  
This datasheet replaces all previous versions



## Technical Properties

### General physical properties

	Typical Value	Test Method
Tape Thickness*	0.155 mm	EN 1942
Adhesive type	Colourless modified acrylic adhesive	
Release liner	Siliconised white paper (90 g/m <sup>2</sup> )	
Carrier type	Black polyester (0.023mm)	
Adhesion to BA steel	1000 cN/20mm	EN 1939
Release value	20 cN/50mm	Nitto Belgium Test Method
Static Shear	0.5 mm/3h	EN 1943
Transport and storage conditions	Temperature 15 °C to 30 °C Relative humidity 40 to 75% RH	

\* Tape thickness = Total thickness without liner  
 Details from the test methods are described on the customer product specification.  
 CAUTION: The above are typical values and should not be used in writing specifications.

### Performance properties

	Typical Value	Test Method
High temperature resistance	150 °C	3 min. 200 g/cm <sup>2</sup>
Dynamic shear	350 N/4cm <sup>2</sup>	Tested after 15 min., 300mm/min
Splicing tack	Medium	Nitto Belgium test method
Probe tack	450 cN/20mm <sup>2</sup>	ASTM D2979

## Warranty

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 6 months thereafter, subject to the conditions set out herein.

## Application guidelines

- Keep the tape in its original packaging until use.
- For optimum results, an even rub down pressure must be applied to the taped area to create the best possible adhesion between tape and the substrates.
- Remove the liner prior to usage.
- The tape should be applied to clean and dry surfaces.
- The best application conditions are obtained at a temperature between 15 °C and 40 °C.

If you require additional information on technical properties and application as well as product sampling or testing, please contact your local Nitto sales office.

General conditions of use and precautions:  
 The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage, the surrounding environment at and after application and time of exterior use. When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

Packaging, transport and storage:  
 During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

Liability:  
 Except for its wilful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits.  
 The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product.

Product information:  
 This datasheet provides a general description of the product properties and application scope. Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

The information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

Nitto Belgium NV has obtained following certificates:

- ISO 9001
- ISO 14001
- IATF 16949

Please check our website for applicable scope

Edition: January 2020  
 Code: DS/01.11/E3 5350B ENG  
 This datasheet replaces all previous versions