



## D2061

### General description

Nitto double-coated tape D2061 consists of a non-woven tissue carrier, coated with a pressure sensitive acrylic adhesive. Mainly used for splicing operations in the cardboard, paper and plastic industry.

### Construction



- Colourless modified acrylic adhesive
- Non-woven carrier
- Colourless modified acrylic adhesive
- Paper release liner

### Characteristics


Nitto D2061 has a good adhesion level, high temperature resistance and shear resistance.

Combined with a good splicing tack makes it suitable for automatic splice operations at high speed, especially on low surface energy materials.

### Application

Nitto D2061 is suitable for flying splice operations on flexible packaging materials, different plastics, special papers, laminated papers and cardboard.

## CORE FUNCTION




TO ADHERE

### Features

- high temperature resistance
- high shear resistance
- high tack on low surface energy materials
- RoHS compliant (2011/65/EC, 2015/863)



Edition: January 2020  
Code: DS/06.09/ D2061 ENG  
This datasheet replaces all previous versions



## Technical Properties

### General physical properties

	Typical Value	Test Method
Adhesive type	Colourless modified acrylic adhesive	
Tape thickness*	0.150 mm	EN 1942
Release liner type/colour	Siliconised havana paper (90 g/m <sup>2</sup> )	
Carrier type	Non-woven	
Release value	30 cN/50mm	Nitto Test Method
Adhesion to BA steel	1000 cN/20mm	EN 1939
Static shear	1.0 mm/3h	EN 1943
Transport and storage conditions	Temperature 15 °C to 30 °C Relative humidity 40 to 75% RH	

\* Tape thickness = Total thickness without liner  
Details from the test methods are described on the customer product specification.

CAUTION: The above are typical values and should not be used in writing specifications.

### Performance properties

	Typical Value	Test Method
Temperature resistance	175 °C	3 min., 200 g/cm <sup>2</sup>
Dynamic shear	370 N/4 cm <sup>2</sup>	Tested after 15 min, 300mm/min
Splicing tack	High	Nitto Belgium Test Method
Probe tack	500 cN/20mm <sup>2</sup>	ASTM D2979

## Warranty

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 6 months thereafter, subject to the conditions set out herein.

## Application guidelines

- Keep the tape in its original packaging until use.
- For optimum results, an even rub down pressure must be applied to the taped area to create the best possible adhesion between tape and the substrates.
- Remove the liner prior to usage.
- The tape should be applied to clean and dry surfaces.
- The best application conditions are obtained at a temperature between 15 °C and 40 °C.

If you require additional information on technical properties and application as well as product sampling or testing, please contact your local Nitto sales office.

General conditions of use and precautions:  
The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage, the surrounding environment at and after application and time of exterior use. When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

Packaging, transport and storage:  
During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

Liability:  
Except for its wilful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits.  
The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product.

Product information:  
This datasheet provides a general description of the product properties and application scope. Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

The information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

Nitto Belgium NV has obtained following certificates:

- ISO 9001
- ISO 14001
- IATF 16949

Please check our website for applicable scope

Edition: January 2020  
Code: DS/07.10/E3 D2061 ENG  
This datasheet replaces all previous versions