


Surface protective materials

SPV-362X-2K2

Outline

SPV-362X-2K2 is suitable for melamine plywood and plastic surface during machine processing with enough adhesion level.

Construction



Acrylic pressure sensitive adhesive
Polyethylene film

Features

- Minimal change in adhesive strength after laminating enables to be easy peeling.
- Minimally affected by surface condition (roughness) of the substrate, applicable for a wide range of substrates.
- Withstand light processing such as shallow drawing and bending, preventing damage during process.
- Light unwinding and easy laminating workability.

Applications

Surface protection for melamine plywood, precoated steel plates and plastic plates during storage, process, and transportation.

SPV-362X-2K2_E

1/3

2023. 1. 30

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.

Standard Size · Color

Item	Thickness (mm)	Width (mm)	Length (M)	Color
SPV-362X-2K2	0.075	1250	200	Clear

*Contact us for information concerning sizes other than the above.

General properties

Item	Unit	SPV-362X-2K2
Thickness *1	mm	0.075
Adhesive Strength *2	N/20mm	1.00
Tensile Strength *3	N/20mm	30
Elongation *3	%	200

Test Method

*1:Nominal thickness

*2:Based on JIS Z-0237

(Adherend: SUS430BA, Tensile speed : 300mm/min, Peeling angle:180°)

*3:Based on JIS Z-0237

SPV-362X-2K2_E

2/3

2023. 1. 30

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.

Precautions

- Duly inspect the adaptability of this product to your intended use, prior to its application.
We may conduct the adaptability test in your favor. However, its content and results do not guarantee your use. It is of your responsibility to ultimately determine its adaptability.
- The characteristics and performance of this product depend on the type of adherend, environment of use, and conditions/period after application. Always test (including the appearance) before changing the adherend (composition/surface roughness), conditions or use.
- When the product is applied to PVC adherends with plasticizer or surface-active adherends (electrolyzed, chemically treated, polished, etc.), it may become difficult to release or tend to leave deposits, as time passes.
- When applying the product to a display material, test with particular attention on appearance defects. Stain, cloudiness or unevenness may appear on the surface of the display material, depending on its type. Traces of air bubbles may be left if they are trapped during application.
- Aforementioned problems may also arise when the product is stored for a long period of time after application.
- Do not use the product outdoors.
- Wipe off any grease, moisture or dust on the adherend before application.
- When coating after the surface protective material has been peeled, products should be used upon giving sufficient consideration to surface washing, below-surface processing and sintering conditions and confirming the adhesiveness of the coating.
- Please note that the surface of the adherend may repel paint or exhibit poor paint adhesion after 362X-2K2 is peeled off.

SPV-362X-2K2_E
3/3
2023. 1. 30

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.