


Varnished Cloth

VC-Y**1. Outline**

Varnished Cloth is one of the electrical insulating materials impregnated with varnish to cotton cloth. (non-adhesive product)

2. Structure**3. Size**

Thickness(mm)	0.18, 0.25
Working width(mm)	900
Length(m)	10 or 50

4. Application

Outer layer insulation of such as transformer and motor

5. Properties

Item	Unit	Thickness		Test Method
		0.18mm	0.25mm	
Thickness	mm	0.182	0.255	micrometer
Tensile strength (Length wise)	N/15mm	146.6	171.7	chuck distance : 200mm tensile speed : 200mm/min
Elongation(Length wise)	%	3.5	5.6	
Break down voltage	normal	10.7	12.1	increased voltage:1000V/sec (heat resistance) after 105 °C×10min
	heat resistance	5.7	10.9	

Contact : Nitto Shinko Corporation Customer Support Center E-Mail tsc-nsk@nitto.co.jp

VC-Y 1/1

1001-66136-150121_E

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.

Nitto Shinko Corporation