


Varnished Teflon™ Cloth Tape**VTT-Y****1. Outline**

Varnished Teflon™ Cloth Tape is one of the electrical insulating materials impregnated with varnish to teflon™ cloth. (non-adhesive product)

2. Structure**3. Size**

| | |
|---------------|------------------------|
| Thickness(mm) | 0.08, 0.10, 0.13, 0.18 |
| Width(mm) | 13, 19, 25 |
| Length(m) | 45 |

4. Application

Outer layer insulation of such as transformer and motor

5. Properties

| Item | Unit | Thickness | | | | Test Method |
|-----------------------------------|--------------------|-----------|--------|--------|--------|---|
| | | 0.08mm | 0.10mm | 0.13mm | 0.18mm | |
| Thickness | mm | 0.083 | 0.104 | 0.135 | 0.190 | micrometer |
| Tensile strength (Length wise) | N/15mm | 92.0 | 94.0 | 90.9 | 198.1 | chuck distance : 200mm tensile speed : 200mm/min |
| Elongation (Length wise) | % | 22.5 | 21.5 | 21.2 | 43.6 | |
| Break down voltage | normal | kV | 7.6 | 9.8 | 10.4 | increased voltage:1000V/sec (heat resistance) |
| | heat resistance | | 6.4 | 8.1 | 8.8 | after 120°C×10min |

"Teflon™" is a registered trademark of TEIJIN LIMITED and Toray Industries, Inc. .

Contact : Nitto Shinko Corporation Customer Support Center E-Mail tsc-nsk@nitto.co.jp

VTT-Y 1/1

1001-10203-240716_E

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.