

Tape which fixes curing material of flooring floor.

NO.395N



Constitution

- Baking : Polyolefin .
- Adhesive : Pressure sensitive acrylic adhesive

Application

- Fixation of flooring floor curing material.



This tape can be used to fix the waving curing paper.



This tape can be used to fix the one to plywood with a strong repulsion.



This tape can be used to fix flooring and the curing paper.

Specialty

- There is almost no paste remainder.
- It can cut easily by hand.

Characteristic

Item□	Unit□	Measurements□
Thickness	mm	0.126
Adhesion strength	N/25mm	8.81
Rewinding force	N/25mm	1.98
Tensile strength	N/10mm	12.6

Doc No. HOU-021-E-1 2013/09/13 1/2

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.

Test method

- According to JIS Z 0237:2000

Precautions

- Wipe oil, moisture, and dust off the surface of adherends thoroughly before application.
- When processing foam/synthetic resin adhesive into ribbons, make sure to cut and process it in lengthwise. If it is cut in widthwise, the tape may stretch when using.
- When processing foam/ butyl rubber adhesive into ribbons, make sure to cut and process it in lengthwise and widthwise. If it is cut diagonally, the tape may stretch when using.
- The adhesive is pressure-sensitive. Handle it with utmost care.
- Most recommended temperature for adhesion is above 10°C. (If the temperature is below 10°C (like in winter), their initial adhesive strength will be low.)
- Place the original roll of these products horizontally for storage to avoid deformation.
- Keep the products away from high temperatures and humidity, and store them in a dark cool place avoiding direct sunlight.
- The numbers in this data sheet are typical measurements in our laboratory, and not guaranteed values.
- Make sure the product is suitable for the application (objective and conditions) before attempting to use. The tape may come off depending on the substrate to which it is applied or conditions under which it is applied.

Doc No. HOU-021-E-1 2013/09/13 2/2

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.