


## Nomex™ Adhesive Tape

# No.380

### 1.Features

- Excellent heatproof property.
- Excellent electric insulation property.
- Base material has 2mils and 3mils.

### 2.Structure



\* Nomex™ is a registered trade name of Du Pont

### 3.Applications

- Interlaminar insulation in transformers
- Termination and outer insulation on coils
- Heat-resistant electrical insulation

### 4.Properties

Table 1 . General properties

Items	Unites	2mils	3mils
Total Thickness	mm	0.11	0.13
Adhesion to Steel	N/19mm	8.5	7.6
Unwinding Force	N/19mm	1.7	1.9
Tensile Strength*1	N/19mm	91	134
Elongation*1	%	9	10
Breakdown Voltage	kV	2.4	3.4
Electrolytic Corrosion Coefficient	-	0.98	0.98

Footnote : \*1 at Breaking

NOMEX™ is a registered trademark of Dupont

Contact : Nitto Shinko Corporation Customer Support Center E-Mail [tsc-nsk@nitto.co.jp](mailto:tsc-nsk@nitto.co.jp)

NO.380 1/1  
5001-27222-140201\_E

**Notes:** This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.