

SURFACE PROTECTION TAPES

SLIPGUARD 4222E

General description

Nitto SLIPGUARD 4222E is a surface protection tape to protect floors and surfaces against staining and abrasion around production areas or during construction work. The unique concept of a special anti-slip white embossed PP carrier combined with a high-tack pressure sensitive emulsion-based acrylic adhesive reduces the risk from falling or slipping and increases the safety level on construction sites.

Features

- Anti-slip film
- Easy to apply
- Good abrasion, tearing and impact resistance
- Easy to remove after use
- Recyclable

Application

Nitto SLIPGUARD 4222E protects all kind of smooth and rougher surfaces, like chipboard, wood and carpet against dust, footprints, construction material, paint and water. The product is also used to protect spray cabins and aircraft wings during repair and maintenance.

Properties

| | Typical value* | Test method |
|-----------------------|------------------------|-------------|
| Film type | Embossed PE film | |
| Adhesive type | Acrylic emulsion-based | |
| Total thickness | 240 µm | EN 1942 |
| Adhesion to BA steel | 400 cN/20mm | EN 1939 |
| Tensile strength MD** | 120 N/20mm | EN 14410 |
| Elongation MD** | 600% | |
| Colour | White | |

*CAUTION: The above are typical values and should not be used in writing specifications. Details from the test methods are described on the customer product specification.

** MD = Machine Direction

SURFACE PROTECTION TAPES

Warranty

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 12 months thereafter, subject to the conditions set out herein.

Availability

Widths: 1030 mm and 1230 mm (untrimmed log rolls)

Lengths: 100 m, 500 m and 1000 m

Please contact us for specific dimensions.

Storage conditions

The product should be protected against direct sunlight and extremes in temperature and humidity. Recommended storage and transport conditions are between 15 °C and 30 °C and between 40% and 75% relative humidity. The product should be stored in its original packaging in a well-ventilated room to avoid deterioration, deformation and contamination. Once removed from its packaging, it should be protected against dust and other impurities. Do not over stack the product, as this may cause deformation.

Lamination guidelines

- These tapes should be applied to clean and dry surface by automatic mechanical means.
- To avoid entrapped air-bubbles, excessive tension and shear, the customer should determine appropriate lamination conditions.
- The best lamination conditions are obtained at a temperature between 15 °C and 40 °C.

Application guidelines

- This tape cannot be used for outside exposure.
- Surface protection tapes are not meant for permanent protection, they should be removed at the end of the supply chain.

SURFACE PROTECTION TAPES

General conditions of use and precautions

The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage, the surrounding environment at and after application and time of exterior use. When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

Packaging, transport and storage

During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

Liability

Except for its willful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits. The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product. Nitto's liability is limited to the terms and conditions provided in the Product Specification and Nitto's General Terms and Conditions of Sale.

Product information

This datasheet provides a general description of the product properties and application scope.

Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

The information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

Nitto Belgium NV has obtained the following certificates

- ISO 9001
- ISO 14001
- ISO 45001