

SURFACE PROTECTION TAPES

SPV 6055L3 HP

General description

SPV 6055L3 HP is a Surface Protection Tape suitable to protect high-gloss stainless steel during mechanical processing, such as deep drawing, bending and punching. This product consists of a blue transparent PO film coated with a special pressure sensitive easy-to-peel emulsion-based acrylic adhesive.

Features

- Emulsion-based
- Low unwind force for easy lamination
- Stable adhesion force for long storage time
- Low adhesion level ideal for high gloss stainless steel
- Excellent tear-resistance film for good deformation behavior
- Easy-to-peel adhesive for fast removability
- Recyclable film

Application

SPV 6055L3 HP is an ideal product for protecting high-gloss stainless steel during mechanical processes, such as deep drawing, bending and punching. The product is especially designed for full automated process lines where high output is a standard. It performs as a real problem solver for very difficult and complex shapes. A specially designed high performance (HP) PO film guarantees good tear resistance in both machine and cross direction, which leads to very minor film burrs during processing. The transparency of this tape allows easy identification and inspection of the protected substrate. The tape features a stable adhesion force over time, ensuring consistency during deformation as well during peel off at the end of the process. This adhesion stability has a big advantage for steel service centers where long storage times can occur. Furthermore, the emulsion-based adhesive will not create staining on the steel surface.

Properties

	Typical value*	Test method
Film type	PO film	n/a
Adhesive type	Acrylic-based	n/a
Total thickness	55µm	EN 1942
Adhesion to BA steel	55 cN/20mm	EN 1939
Tensile strength MD** Tensile strength CD**	35 N/20mm 25 N/20mm	EN 14410
Elongation MD** Elongation CD**	550% 650%	
Color	Blue transparent	n/a

*CAUTION: The above are typical values and should not be used in writing specifications. Details from the test methods are described on the customer product specification.

**MD = Machine Direction, CD = Cross Direction.

SURFACE PROTECTION TAPES

Warranty

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 12 months thereafter, subject to the conditions set out herein.

Availability

Widths: max 1540 mm

Lengths: 1000 m

Please contact us for specific dimensions.

Storage conditions

The product should be protected against direct sunlight and extremes in temperature and humidity. Recommended storage and transport conditions are between 15 °C and 30 °C and between 40% and 75% relative humidity. The product should be stored in its original packaging in a well-ventilated room to avoid deterioration, deformation and contamination. Once removed from its packaging, it should be protected against dust and other impurities. Do not over stack the product, as this may cause deformation.

Lamination guidelines

- This tape should be applied to clean and dry surface by automatic mechanical means.
- To avoid entrapped air-bubbles, excessive tension and shear, the customer should determine appropriate lamination conditions.
- The best lamination conditions are obtained at a temperature between 15 °C and 40 °C.

Application guidelines

- In general, this tape is immediately usable for further processing after lamination.
- This tape is not designed for outside exposure.
- Surface protection tapes are not meant for permanent protection, they should be removed at the end of the supply chain.

SURFACE PROTECTION TAPES

General conditions of use and precautions

The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage, the surrounding environment at and after application and time of exterior use. When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

Packaging, transport and storage

During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

Liability

Except for its willful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits. The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product. Nitto's liability is limited to the terms and conditions provided in the Product Specification and Nitto's General Terms and Conditions of Sale.

Product information

This datasheet provides a general description of the product properties and application scope.

Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

The information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

Nitto Belgium NV has obtained the following certificates

- ISO 9001
- ISO 14001
- IATF 16949