

P-790

PAPER MASKING TAPE

PRODUCT DESCRIPTION

General purpose crepe paper masking tape coated with a synthetic rubber designed for a vast array of every day, room temperature masking and holding applications. This product is ideal in the housing and construction, aerospace, automotive and industrial applications.

FEATURES

- Offers high hold and high adhesion to a wide range of plastic, metal and wood surfaces.
- The adhesive is strongly secured to the backing, permitting smooth applications and easy removal.
- No adhesive transfer with an easy to write on paper backing for making mark ups.

PRODUCT CONSTRUCTION

RELEASE COAT
IMPREGNATED CREPE PAPER
SYNTHETIC RUBBER/RESIN

APPLICATION

- Designed for all purpose uses in room temperature masking projects.
- Used in light duty packaging, bundling, tabbing, roll start up and light splicing applications

PROPERTIES, CERTIFICATIONS AND SPECIFICATIONS

Backing Material	Impregnated Crepe Paper	
Adhesive	Synthetic rubber/ Resin	
Color	Tan	
	Imperial	Metric
Total Tape Thickness	5.0 mil	0.127 mm
Tensile Strength	23 lbs/in	80.55 N/20 mm
Elongation	8%	
Adhesion to Steel	48 oz/in	10.51 N/20 mm
Certifications	ISO /IATF/AS: https://www.nitto.com/us/en/about_us/Americas/americas_certification/	
Government Specifications	ASTM D6123 (Replaces obsolete PPP-T-42C Type I, CID A-A-883 Type I)	

*CAUTION: The above are typical values and should not be used in writing specifications. Customer is responsible to ensure product meets intended application requirements before approved for use.

SHELF LIFE & GENERAL STORAGE CONDITIONS

The general shelf life and storage conditions for this Nitto, Inc. product are as follows:

- Shelf life for this product is TWELVE MONTHS FROM DATE OF SHIPMENT.
- Best stored between 50°F-80°F / 10°C-27°C, 25-50% relative humidity; out of direct sunlight.

PRECAUTION REMINDER

Surface should be clean, free of oil, moisture and dirt before applying. Pressure-sensitive adhesive tapes may require pressure by roller, hand or press when applying. Not doing so may affect the general properties and appearance. Please inspect your surface prior to application; this tape may not adhere well to extremely uneven or distorted surfaces. Please remember to allow adequate time for full adhesive strength.

WARRANTY INFORMATION

Unless Nitto agrees otherwise in a written agreement signed by Nitto, the warranty information and other terms of sale can be found in the Nitto Terms and Conditions of Sale in the legal section of www.nitto.com and are hereby incorporated by reference.

TECHNICAL SUPPORT

For questions pertaining to this data sheet or for additional product information; please email us directly at support.us@nitto.com